

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
5 February 2004 (05.02.2004)

PCT

(10) International Publication Number
WO 2004/012206 A2

- (51) International Patent Classification⁷: **G21F**
- (21) International Application Number:
PCT/US2003/023491
- (22) International Filing Date: 29 July 2003 (29.07.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/398,808 29 July 2002 (29.07.2002) US
- (71) Applicant (for all designated States except US): **THE C & M GROUP, LLC** [US/US]; 8225 Madrillon Estates Drive, Vienna, VA 22182 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **CARSON, Roger, W.** [US/US]; 8225 Madrillon Estates Drive, Vienna, VA 22182 (US). **BREMER, Bruce, W.** [US/US]; 18300 Feathertree Way, Apartment 304, Montgomery Village, MD 20886-6318 (US).
- (74) Agents: **WRAY, James, C. et al.**; Suite 300, 1493 Chain Bridge Road, McLean, VA 22101 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **MEDIATED ELECTROCHEMICAL OXIDATION USED FOR THE DESTRUCTION OF ORGANICS CONTAMINATED WITH RADIOACTIVE MATERIALS, DISSOLUTION OF TRANSURANICS, AND THE DECONTAMINATION OF EQUIPMENT CONTAMINATED WITH MIXED WASTE**



(57) Abstract: A mixed waste mediated electrochemical oxidation process (MEO) process and apparatus for the dissolution of transuranic elements (e.g., plutonium, neptunium, americium, curium, and californium), and/or compounds thereof in transuranic waste (TRUW), low level waste (LLW), low level mixed waste (LLMW), special case waste (SCW), and greater than class C (GTCC) LLW's, and also the destruction of the non-fluorocarbon (e.g., PTFE) organic component in the waste. The MEO process and apparatus operates in three different modes; dissolution, destruction, and decontamination. Non-radioactive materials combined in the waste are part of the mixed waste. The principle components of mixed waste of concern are the organic materials that are contaminated with radioactive compounds. In the first mode, dissolution, the process runs until the transuranics such as a mixed oxide or carbide, and/or mixture of oxides or carbides of uranium and plutonium are totally dissolved into solution. The

second mode destruction, the process is operated such that the mixed waste materials are reduced to a CO₂, water and small amounts of inorganic salts. The third mode decontamination, involves contaminated equipment, instruments, glassware, containers (drums and equipment). In the decontamination mode the MEO process destroys the mixed wastes that have contaminated the equipment. In the mediated electrochemical oxidation process one or more regenerable oxidizing redox couples (specified in Tables I and II) interact with the mixed waste to decompose it. The oxidizers are present in electrolytic solutions that are acidic, alkaline, or neutral, operating in the temperature range of slightly above freezing to slightly below boiling point of the electrolyte at one atmosphere.